

Self-Serve

Standard Features

- High-Pressure Soap
- High-Pressure Wax
- Low-Pressure Presoak
- Low-Pressure Tire Cleaner
- High-Pressure Rinse
- Manual Override
- Rotary Coin Boxes
- Slugbuster Coin Acceptors
- Accutimers
- Vaults
- 180° and 360° Booms

Revenue-Enhancing Options

- Touch-Pad Doors
- Credit Card Acceptor
- Bill Acceptor
- Spot Free Rinse
- HP Rinse Temperature Selection
- Wheel Cleaner
- Bug Cleaner
- Glass Cleaner
- Bubble Brush
- Tri-Foam Bubble Brush
- Foaming Conditioner
- Tri-Foam Conditioner
- Plus Full Selection of In-Bay Options

Other Options

- Weep (manual or automatic)
- Antifreeze Injection

AquaSpray® Self-Serve: Compact Design with Easy Access

Mark VII offers the next generation in self-serve carwash performance and profitability: AquaSpray. Self-serve operators can take advantage of the same innovative technology, advanced research and development, and commitment to quality that has made Mark VII a leader in in-bay automatic carwash systems. And for those short on real estate in the equipment room, AquaSpray offers up to a 50% space savings over competing systems!

AquaSpray continues the Mark VII tradition of unparalleled performance and value. It boosts profitability for operators by giving the motorist more selections—and more ways to spend money—than ever. AquaSpray puts a high priority on the reason you're in the business in the first place: driving revenue and return on investment.

More of Everything That You and Your Customers Want

AquaSpray Self-Serve drives profitability with more wash options, more features, and more effective merchandising than competing systems. Customers looking for wash options find eleven of them at the feature-rich coin box. Additional eye-catching signage explains all features in a friendly, inviting style. And AquaSpray's state-of-the-art, high-tech mechanical design delivers the most robust and adjustable wash presentation possible.

Reliability Built-In

With over 40 years' experience in engineering carwash performance, Mark VII knows how to keep your operation up and running. Modular design, quality stainless steel construction, and high-quality copper and stainless components add up to a reliable workhorse that excels in any environment.

Mark VII's innovative layout provides front-panel access to many slide-out components for easy installation, set-up and service. Color-coded hoses and wiring allow spot access instead of tracing from the source throughout the installation. Everything is designed for trouble-free performance and simplified maintenance.



AquaSpray Self-Serve.

Control Everywhere You Need It

Centralized control puts the adjustments for an entire installation in a single location. Fully quantifiable inputs provide complete adjustability of chemical concentrations and flow rates. You can compensate for different line distances to maintain profitability with more consistent presentation. You can even specify the order of the customer selections on the modular coin box as you see fit, thanks to customizable die-cut graphics and modular assembly.

The Latest in a Long Line of Profitable Carwash Products

If your goal is an efficient, reliable and profitable self-serve operation, AquaSpray is your choice. Highest quality design and construction, unparalleled reliability, and outstanding mechanical design help you build profits from day one. Take advantage of AquaSpray's superior technology, reliability, and profit potential. Ride the high road to making more money, with carwash technology you can count on.

- **Increase bay time for more profitability.**
- **Compact design with easy access.**
- **Centralized control and pump assembly for easy adjustment and maintenance.**
- **Infinitely adjustable settings provide maximum control.**
- **Slide-out modules for easy service.**



Specifications:

MACHINE DIMENSIONS (FOR 6-BAY CONFIGURATION)

	Pumping Plant	Fluid Module
Height	81"	81"
Width	56"	36"
Depth	36"	36"

ELECTRICAL SERVICE

20 amps + 20 amps/bay for
5 hp at 208-230 VAC, 3ø
20 amps + 15 amps/bay for
3 hp at 208-230 VAC, 3ø
20 amps + 20 amps/bay for
3 hp at 220-240 VAC, 1ø

AIR AND WATER

Min. Water feed pressure	40 PSI
Max. Water feed pressure	85 PSI
Min. Water demand	5 GPM/bay
Air demand	1.5 CFM/bay at 40 PSI

Note: The above specifications do not include accessory items such as water heaters, vacuums, water softeners, bill changers, etc.